



WOODCO

**SPECIFICATIONS**

COLOR/SHADE	WHITE-LIGHT
CONSTRUCTION	ENGINEERED WALLBOARD
WEAR LAYER	_____
PLYWOOD	100% BALTIC BIRCH MULTIPLY PLYWOOD
FINISH	10% VARNISH GLOSS
PATTERN	INTERLOCKING SYSTEM
JANKA/HARDNESS	_____
SPECIES	MAPLE
THICKNESS	8.5 mm - 10 mm
WIDTH	14" (35.56 cm)
LENGTH	44" (111.76 cm)
MOISTURE CONTENT	_____
COLLECTION	WALLS & CEILINGS
ORIGIN	NORTH AMERICA
GRAIN	MIXED

**SURFACE BURNING CHARACTERISTICS**

CLASSIFICATION	CLASS B OR II
FLAME SPREAD (FSI)	75
SMOKE DEVELOPED (SDI)	350

**DESNA 3D WALLBOARD DESCRIPTION**

Engineered Maple 3D wall paneling.

Invitation to poetry, brightness and enlightenment of a room, this impression of lightness confers a warm and soft contemporary feel all at once with the ubiquity of white punctuated by various shades of gray that enlarge your space.

**OPTIONS & UPGRADES**

- Non-Customizable
- Also available in a Peel & Stick wall paneling  
- See Pearl 3D Wallboard

**FIRE RATING**

Flame spread / Smoke developed Index is a result (or the average if the results of multiple tests), rounded to the nearest 5. Smoke developed results in excess of 200 are rounded to the nearest multiple of 50.