

SPECIFICATIONS	
COLOR/SHADE	BROWN/LIGHT-DARK
CONSTRUCTION	ENGINEERED FLOORING
WEAR LAYER	4mm
PLYWOOD	100% BALTIC BIRCH MULTIPLEX PLYWOOD
FINISH	UV OILED
PATTERN	TONGUE & GROOVE
JANKA/HARDNESS	1360
SPECIES	RECLAIMED OAK
THICKNESS	5/8"
WIDTH	RANDOM 4" - 7"
LENGTH	RANDOM 2' - 10'
MOISTURE CONTENT	8 - 12%
COLLECTION	MAYFLOWER
ORIGIN	USA
KNOT CONTENT	SOME KNOTS
HOLE CONTENT	FILLABLE
HEARTWOOD CONTENT	90%
CHECKING	MINIMAL
GRAIN	MIXED
GRADING	CHARACTER
LEED CREDITS	MR 4.1 & 4.2 (Material reuse) MR 5.1 & 5.2 (Material)

NORMAC PLANK DESCRIPTION

Reclaimed Oak Flooring Skipped Planed Patina Face Invisible UV Oil Finish.

Oak was a very common material used to construct barns and buildings in Eastern USA in the 18th century. Oak is a durable and classic option.

OPTIONS & UPGRADES

- Wire Brushed Option—Available upon request
- Custom Thickness—Available upon request
- Custom Widths—Available upon request
- Edge Milling Options—Available upon request

