



WOODCO

PRODUCT CODES

NOSING	WC710
RISER	WC722
TREAD	WC734

SPECIFICATIONS

COLOR/SHADE	BROWN/LIGHT
CONSTRUCTION	STAIR PARTS
WEAR LAYER	_____
PLYWOOD	_____
FINISH	UNFINISHED
PATTERN	STAIR PARTS
JANKA/HARDNESS	1360
SPECIES	WHITE OAK
THICKNESS	SEE CHART
WIDTH	SEE CHART
LENGTH	STANDARD 36", 48", 60"
MOISTURE CONTENT	8 - 12%
COLLECTION	STAIR PARTS
ORIGIN	USA
KNOT CONTENT	SMALL TIGHT KNOTS
HOLE CONTENT	FILLABLE
HEARTWOOD CONTENT	90%
CHECKING	NONE
GRAIN	MIXED
GRADING	SELECT
LEED CREDITS	_____

WHITE OAK STAIR PARTS DESCRIPTION

Character Grade Plain Sawn White Oak Stair Parts.

Oak is a very strong stable lumber with a very consistent grain pattern. Plain Sawn Oak, also known as Flat Sawn Oak, is the most common way of cutting oak logs. It creates the least waste and is known for the tangential grain and the cathedral pattern on the face of the board.

STANDARD SIZES

- Nosing: 1 1/16" (Thickness) x 3 1/2" (Depth)
- Riser: 3/4" (Thickness) x 7 1/4" (Height)
- Tread: 1 1/16" (Thickness) x 11 1/4" (Depth)
- Custom sizes and shapes—Available upon request

PLEASE SPECIFY LENGTH WHEN ORDERING.



Bullnose



Eased Edge

WORLDWIDE SOURCE FOR WOOD

1210 ARION PARKWAY SAN ANTONIO TX 78216 | 210.298.9663 | WWW.WOODCO.COM | INFO@WOODCO.COM